

SPS系列 选粉机

CLASSIFIER



产品特点 Product Advantages

- 提高产量，节能降耗：粉磨系统产量可提高30-50%，单位能耗降5%-20%。
Increase production and save energy: the output of the grinding system can increase by 30-50%, and unit energy consumption can be reduced by 5%-20%.
- 提高质量，降低成本：提高了粒径范围3-30mm的颗粒含量增加，有助于提高水泥强度，增加矿渣掺量，减少熟料用量。
Improve quality and reduce costs: increased particle size range of 3-30mm increases the content, which helps to improve cement strength, increase slag content, and reduce the amount of clinker used.
- 操作简单，细度调节方便灵活：主电机和润滑油站可远程控制，只需调节主电机转速即可改变产品的细度，物料的颗粒分布、风量、机内温度可任意调整。
Simple operation and convenient fine adjustment: the main motor and lubricating oil station can be remotely controlled. By adjusting the speed of the main motor, the fineness of the product can be changed. The particle distribution, air volume, and internal temperature of the material can be adjusted arbitrarily.
- 设备处理量大：回磨粗粉料中的细粉残留量极少，即其特劳姆曲线很陡，处理量大。
Large equipment processing capacity: there is very little fine powder residue in the returned coarse powder material, which means its specific performance curve is steep and the processing capacity is large.

SPS系列 选粉机

CLASSIFIER



扫一扫视频号获取更多资讯

型号 Model			SPS75PCM	SPS75PCM	SPS75PCM	SPS75PCM	SPS75PCM
选粉机 Classifier	产量 Output (t/h)	水 泥 Cement	19-36	29-55	38-62	55-95	85-110
		生 料 Raw material	27-51	41-78	54-88	78-135	108-165
	喂料量 Feeding (t/h)	水 泥 Cement	95	145	190	272	372
		生 料 Raw material	135	205	270	390	540
	选 粉 风 量 Powderselectionairvolume(m³/s)		3-4	4.5-5.5	6-7	9-11	12-15
	设 备 阻 力 Equipmentresistance(kPa)		3.5-4	3.5-4	3.5-4	3.5-4	3.5-4
减速机 Reducer	型号 Model		B2SV-2	B2SV-2	B2SV-2	B2SV-2	B2SV-2
	速比 Speed Ratio		5	5	5.6	6.3	6.3
电机 Motor	型号 Model		Y160L-2	Y200L-2	Y225M-4	Y280S-4	Y280M-4
	功率 Power kW		18.5	30	45	75	90
循环风 Circulating air	型号 Model		G5-48No11.5D	G5-48No12.5D	G5-47No12.5D	G4-73No14D	G4-73No14D
	转速 Rotational speed (rpm)		1450	1450	1450	1450	1450
	风量 Airflow(m³/h)		37359	58485	70410	108302	154919
	风压 Wind pressure(pa)		4635	4782	4924	4840	4990
	电机型号 Model		Y280S-4	Y315S-4	Y315M-4	Y315M1-4	Y355M2-4
	功率 PowerkW		75	110	132	185	280
稀油站 Thin oil station	型号 Model		XYZ-6G	XYZ-6G	XYZ-10G	XYZ-10G	XYZ-10G
	流量 Flow rate(L/min)		6	6	10	10	10

根据公司不断改进产品的方针, 我们保留在未事先通知用户的情况下, 改变参数和设计的权力, 文中插图并不是设备的标准款式, 山河普石勒保留最终解释权。
The parameters and design could be modified according to our upgrading plan. The illustration is not indicating the standard equipment. All rights reserved by Sunward•PSR.

